

# P65WK Portable Air Compressor

**IR** Ingersoll-Rand®



## Exceeds Your Standards for Efficiency and Performance

This quiet-running, fuel-efficient portable compressor doesn't sacrifice performance. With a compact, lightweight design, stable highway towing, powerful Kubota engine, and a noise rating that exceeds EPA requirements, you can get the job done — reliably, safely, and efficiently. This newest addition to the Ingersoll-Rand compressor line is well-suited for powering your pneumatic tools.



# P65WK Portable Air Compressor

## Specifications

### KEY FEATURES / BENEFITS

- High-performance, quiet-running, fuel-efficient Kubota engine
- Simple key start sequence
- Environmental contamination is minimized by a drip-proof base which helps prevent fluid spillage
- Quick and easy service access reduces maintenance time and life-cycle operating cost
- Integrated automatic safety shutdown features
- Compact and lightweight design with excellent highway towing stability
- Based on a zinc phosphate preparation process, the metal enclosures are powder-coat finished offering excellent resistance to corrosion and abrasion
- Exceeds EPA noise guidelines at 71 dBA

### INGERSOLL-RAND PNEUMATIC TOOLS

TOOL	MODEL	SIZE / WEIGHT	CFM
Paving Breaker	PB35AL8	40 lb	48
Diggers	93LA 1	23 lb	45
	95LA 1	28 lb	47
Rivet Busters	9001	25 lb	40
	9001A	25 lb	40
Chippers	2A2SA	16 lb	28
	3A2SA	17 lb	29
	W2A2	16 lb	28
	W1	15 lb	28
	W2	15 lb	28
	W3	16 lb	29
Tampers	341A2M	35 lb	29
	130A1M	12 lb	14
Large Drills	22MA2	7/8"	55
	22KWA1	9/16"	55
Maintenance	728LA2	3/8"	19
Drills	728NA3	1/2"	19
Rammers	130AIM	12 lb	14
	241AIM	27 lb	29
Impact Wrenches	1702PI	3/8"	15
	2131P	1/2"	24
	2707AI	1/2"	26
	1720PI	3/4"	40
Grinders	CD250RG4	.35 hp	12
	TD250RG4	.70 hp	26
	HD180RG4	1.0 hp	43

### MODEL

**P65WK**

### ENGINE — TIER 2

Make	Kubota
Model	D1005
Number of Cylinders	3
Full Load Speed rpm	3,000
Power hp (kW)	23.5 (17.5)
Electrical	12 V
Cooling	Water
Fuel Tank Capacity gal (L)	6.8 (25.7)

### COMPRESSOR — ROTARY SCREW / SINGLE STAGE

Free-Air Delivery cfm (m <sup>3</sup> /min)	65 (1.9)
Rated Operating Pressure psi (bar)	100 (7)
Max Allowable Pressure psi (bar)	125 (8.6)
Air Outlets	2 x 3/4"

### TIRES

Tire Size	155 R 13
Number of Wheels	2

### SOUND LEVEL DATA

Guaranteed Sound Power Level, Tested	71 dBA
--------------------------------------	--------

### DIMENSIONS WITH RUNNING GEAR

Overall Length — With Fixed Towbar in (mm)	108.2 (2750)
Overall Width in (mm)	46.7 (1185)
Height in (mm)	45.4 (1154)
Ground Clearance in (mm)	9.0 (230)
Weight (net) Fixed Towbar lb (kg)	948.0 (430)

Product improvement is a continuing goal at Ingersoll-Rand. Designs and specifications are subject to change without notice or obligation.

### WARRANTY

1-year / 2,000-hour warranty on all components, except engines, tires, and batteries which carry the manufacturer's warranty.

### AIREND

2-year / 4,000-hour warranty on airend, extended to 5-year / 10,000-hour warranty when original Ingersoll-Rand filters, fluids, and parts are used at the prescribed intervals.

### ENGINE

2-year / 2,000-hour full warranty  
3-year / 3,000-hour parts only warranty